

WHAT IS CLAIMED IS:

1. A method of communicating with an element within an enterprise network, comprising:

5 at a first client, encapsulating a first point-to-point protocol signal within a network address request header; and

communicating the network address request encapsulated signal toward a tunneling server.

10 2. The method of Claim 1, wherein the network address request header comprises a Dynamic Host Configuration Protocol DISCOVER header or a Bootstrap Protocol REQUEST header.

15 3. The method of Claim 1, wherein communicating the network address request encapsulated signal toward a tunneling server comprises communicating the signal toward a router configured to relay network address requests to the tunneling server without referencing a routing table
20 indexed by data channel addresses.

4. The method of Claim 3, wherein the first point-to-point protocol signal comprises a control channel address of a second client, the control channel address
25 being different from any data channel address recognized by the router.

5. The method of Claim 1, wherein the first point-to-point protocol signal comprises a payload including
30 information to be applied to an application residing at a second client.

6. The method of Claim 5, wherein the application residing at the second client comprises a maintenance application operable to diagnose operational characteristics of the second client.

5

7. The method of Claim 1, wherein the first point-to-point protocol signal comprises a payload including at least a portion of an application to be installed on a second client.

10

8. The method of Claim 1, further comprising encapsulating the first point-to-point protocol signal within a tunneling header prior to encapsulating the first point-to-point protocol signal within the network address request header, the tunneling header operable to facilitate a tunneling session between the first client and the tunneling server.

15

9. The method of Claim 8, wherein the tunneling header comprises a tunneling header selected from the group consisting of a Layer Two Tunneling Protocol (L2TP) header, a Point-to-Point Tunneling Protocol (PPTP), or a Layer Two Forwarding (L2F) header.

20

10. The method of Claim 1, further comprising receiving a network address response encapsulated signal from the tunneling server, the network address response encapsulated signal comprising a second point-to-point protocol signal responsive to the first point-to-point protocol signal and encapsulated within a network address response header.

25

30

11. The method of Claim 1, wherein the network address response header comprises a Dynamic Host Configuration Protocol OFFER header or a Bootstrap Protocol RESPONSE header.

12. A computer readable medium operable to execute the following steps on a processor of a computer:

at a first client, encapsulating a first point-to-point protocol signal within a network address request header; and

communicating the network address request encapsulated signal toward a tunneling server.

13. The computer readable medium of Claim 12, wherein communicating the network address request encapsulated signal toward a tunneling server comprises communicating the signal toward a router configured to relay network address requests to the tunneling server without referencing a routing table indexed by data channel addresses.

14. The computer readable medium of Claim 13, wherein the first point-to-point protocol signal comprises a control channel address of a second client, the control channel address being different from any data channel address recognized by the router.

15. The computer readable medium of Claim 12, wherein the first point-to-point protocol signal comprises a payload including information to be applied to an application residing at a second client.

16. The computer readable medium of Claim 12, wherein the first point-to-point protocol signal comprises a payload including at least a portion of an application to be installed on a second client.

17. The computer readable medium of Claim 12, further comprising encapsulating the first point-to-point protocol signal within a tunneling header prior to encapsulating the first point-to-point protocol signal within the network address request header, the tunneling header operable to facilitate a tunneling session between the first client and the tunneling server.

18. The computer readable medium of Claim 12, further comprising receiving a network address response encapsulated signal from the tunneling server, the network address response encapsulated signal comprising a second point-to-point protocol signal responsive to the first point-to-point protocol signal and encapsulated within a network address response header.

19. A method of tunneling in an enterprise network comprising a plurality of clients coupled to a tunneling server by at least one router, the method comprising:

at a first client, generating point-to-point protocol
5 signal;

encapsulating the point-to-point protocol signal
within a network address request header;

communicating the network address request encapsulated
tunneling signal toward a tunneling server operable to
10 identify and remove the network address request header, to
encapsulate the point-to-point protocol signal within a
network address response header, and to communicate the
network address response encapsulated signal toward a
second client.

20. The method of Claim 19, communicating the network
address request encapsulated tunneling signal toward a
tunneling server comprises communicating the signal toward
a router operable to relay the signal toward the tunneling
20 server without referencing a routing table indexed by data
channel addresses.

21. The method of Claim 20, wherein the point-to-
point protocol signal comprises a control channel address
25 of a second client, the control channel address being
different from any data channel address recognized by any
router coupled to the tunneling server.

22. The method of Claim 19, further comprising
30 encapsulating the point-to-point protocol signal within a
tunneling header prior to encapsulating the point-to-point
protocol signal within the network address request header,
the tunneling header operable to facilitate a tunneling
session between the first client and the tunneling server.

10

Year	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100																																																																																																																																																																																																																																		
1990	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99	100	101	102	103	104	105	106	107	108	109	110	111	112	113	114	115	116	117	118	119	120	121	122	123	124	125	126	127	128	129	130	131	132	133	134	135	136	137	138	139	140	141	142	143	144	145	146	147	148	149	150	151	152	153	154	155	156	157	158	159	160	161	162	163	164	165	166	167	168	169	170	171	172	173	174	175	176	177	178	179	180	181	182	183	184	185	186	187	188	189	190	191	192	193	194	195	196	197	198	199	200	201	202	203	204	205	206	207	208	209	210	211	212	213	214	215	216	217	218	219	220	221	222	223	224	225	226	227	228	229	230	231	232	233	234	235	236	237	238	239	240	241	242	243	244	245	246	247	248	249	250	251	252	253	254	255	256	257	258	259	260	261	262	263	264	265	266	267	268	269	270	271	272	273	274	275	276	277	278	279	280	281	282	283	284	285	286	287	288	289	290	291	292	293	294	295	296	297	298	299	300	301	302	303	304	305	306	307	308	309	310	311	312	313	314	315	316	317	318	319	320	321	322	323	324	325	326	327	328	329	330	331	332	333	334	335	336	337	338	339	340	341	342	343	344	345	346

24. In an enterprise network comprising at least one client coupled to a tunneling server by a router having a routing table indexed by data channel addresses, a first client comprising:

5 a protocol stack operable to generate a first point-to-point protocol signal; and

 a tunneling module operable to encapsulate the first point-to-point encapsulated signal within a network address request header;

10 wherein the first client is operable to communicate the network address request encapsulated signal toward the router for forwarding to the tunneling server without reference to the routing table.

15 25. The first client of Claim 24, wherein the network address request header comprises a Dynamic Host Configuration Protocol DISCOVER header or a Bootstrap Protocol REQUEST header.

20 26. The first client of Claim 24, wherein the network address request encapsulated signal comprises a tunneling header encapsulating the first point-to-point signal, the tunneling header operable to facilitate a tunneling session between the first client and the tunneling server.

25 27. The first client of Claim 26, wherein the tunneling header comprises a tunneling header selected from the group consisting of a Layer Two Tunneling Protocol (L2TP) header, a Point-to-Point Tunneling Protocol (PPTP),
30 or a Layer Two Forwarding (L2F) header.

28. The first client of Claim 24, wherein the first point-to-point protocol signal comprises:

an identification of a second client coupled to the tunneling server; and

5 information to be applied to an application residing at the second client.

29. The first client of Claim 28, wherein the identification of the second client comprises a control
10 channel address of the second client, the control channel address being distinct from any data channel address used to index a routing table accessible to the router.

30. The first client of Claim 28, wherein information
15 comprises information to be applied to a maintenance application residing at the second client and operable to diagnose operational characteristics of the second client.

31. The first client of Claim 24, wherein the
20 tunneling module is operable to receive a point-to-point protocol signal encapsulated within a network address response header, the network address response encapsulated signal having been relayed from the tunneling server through the router without reference to a routing table
25 indexed by data channels.

32. The first client of Claim 31, wherein the network address response header comprises a DHCP OFFER header or a Bootstrap Protocol RESPONSE header.

33. In an enterprise network, a client having an enterprise protocol stack operable to process signals received from a data channel and associated with a data channel address, the client comprising:

5 a tunneling module operable to receive a first point-to-point protocol signal encapsulated within a network address response header and to remove the network address response header to expose the first point-to-point protocol signal; and

10 a private protocol stack operable to receive the first point-to-point protocol signal from the tunneling module and to communicate at least a portion of a payload of the first point-to-point protocol signal to a socket layer coupled to an application residing at the client.

15 34. The client of Claim 33, wherein the network address response header comprises a Dynamic Host Configuration Protocol OFFER header or a Bootstrap Protocol RESPONSE header.

20 35. The client of Claim 33, wherein the application comprises a maintenance application operable to diagnose operational characteristics of the second client.

25 36. The client of Claim 33, wherein the application comprises an application operable to process the at least a portion of the payload and to generate an output to be communicated toward another network element.

30

37. The client of Claim 33, wherein:

the private protocol stack is operable to generate a second point-to-point protocol signal comprising a payload carrying at least a portion of the output; and

5 wherein the tunneling module is operable to encapsulate the second point-to-point signal within a network address request header and communicate the network address request encapsulated signal to a router for relaying toward a destination network element without
10 reference to a routing table indexed by data channel addresses.

38. The client of Claim 37, wherein the network address request header comprises a Dynamic Host
15 Configuration Protocol DISCOVER header or a Bootstrap Protocol REQUEST header.

39. The client of Claim 33, wherein the first point-to-point protocol signal is encapsulated within a tunneling
20 header and further encapsulated within the network address response header, and wherein the tunneling module is operable to process the tunneling header to maintain a tunneling session between the client and a tunneling server.

25 40. The client of Claim 39, wherein the tunneling header comprises a tunneling header selected from the group consisting of a Layer Two Tunneling Protocol (L2TP) header, a Point-to-Point Tunneling Protocol (PPTP), or a Layer Two
30 Forwarding (L2F) header.